

AEMCMK-HF D / AXQJ-EMC D / IFSI-EMC-AI D

Aluminium power cable EMC

0,6/1 (1,2) kV



Aluminium power cable for fixed installations indoors and outdoors. May be buried directly in soil. EMC shielded cable gives an excellent protection against electromagnetic disturbances. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Dca-s2,d2,a2.

Standards	SFS 5546, SEK TS 424 14 18-1, HD 604 5 I & D, IEC 60502-1
Reaction to fire	Dca-s2,d2,a2; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Sector shaped stranded aluminium, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Core identification	Blue, brown, black, grey
Oversheath	UV-protected polyolefin compound, Black
Size	4x300/88
Product code	1149224
Nominal cable diameter mm	59
Nominal cable weight kg/km	5427
During handling and installation, cable cm	72
In final installation, cable cm	50
Max. DC resistance of conductor at 20 °C Ω/km	0,100
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 500
Electricity number	6438176226070
EAN code	6438176226070