

AXMK/PE PowerRex PE

Aluminium power cable

0,6/1 (1,2) kV



Aluminium power cable for fixed installations outdoors. May be buried directly in soil, also by ploughing. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free, but without fire protection. The cable is not CPR-classified.

Standards	SFS 5800, SEK TS 424 14 18-1, HD 603 5 E & O
Certificates	SGS Fimko FI 41546
Conductor	Sector shaped stranded aluminium, EN/IEC 60228 class 2
Product Environmental Profile	PEP NXNS-00450-V01.01-EN
(A1-A3) GWP figure kgCO2e/km	3696
Insulation	UV-protected cross-linked polyethylene XLPE
Core identification	Yellowgreen, brown, black, grey
Oversheath	UV-protected polyethylene compound PELLD, Black
Size	4x35 S PowerRex PE
Product code	1116042
Nominal cable diameter mm	22
Nominal cable weight kg/km	571
During handling and installation, cable cm	27
In final installation, cable cm	19
Max. DC resistance of conductor at 20 °C Ω/km	0,868
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-20
standard packing m	Drum 500
Electricity number	6438176300244
EAN code	6438176300244